

H.264 IP 2 MEGA PIXEL CMOS FISH-EYE LENS VANDAL DOME IP-MP096-FE/12V

Feature

- 2 Mega pixel (1600 x 1200) progressive scan
- Built-in Fish-Eye lens can select Panorama
- Software for 180° / 360° angle view
- H.264/MPEG-4/JPEG triple streams simultaneously
- Vandal proof & IP 66
- Up to 32G SD card recording for alarm trigger & network outage
- 2-way audio
- Mobile view support
- PoE support



IP cam

Server	Network Compression	Triple streams:H.264/MPEG-4/JPEG
	Pixel (H x V)	1600x1200, 1280x1024, 1280x960, 1280x720, 800x592,640x480, 320x240, 176x144
	Traffic Control	32/48/64/96/128/196/256/320/384/448/512/576/640/704/768Kbps 1/1.5/2/2.5/3/3.5/4/6/8Mbps
	Max. Frame Rate	Max. 30FPS (1280x720, 800x592, 640x480, 320x240, 176x144), 25FPS (1280x960), 22FPS (1280x1024), 15FPS (1600x1200)
	Safety	User-ID and password
	Protocol	TCP, UDP, IP, HTTP, FTP, SMTP, DHCP, PPPoE, DNS, DDNS, NTP, UPnP, UPnP forwarding, RTSP
	Number of User	Max. 10 connections for singal video
	Storage Capacity	SD card
	Alerting	SMTP, FTP, HTTP, SD card
	Pre / Post Alarm	Pre (0,1,2,3,4,5), post(0,1,2,3,4,5,10) seconds
Release for alarm	Motion detection, I/O or schedule	
Network Camera	Image Pick-up Device	1/3" Progressive Scan CMOS sensor, approximately 2 mega pixel
	BLC	Auto (ON/OFF)
	Electronic Shutter	1/50 (1/60) ~ 1/100,000 second
	Video Output	1Vp-p, 75 Ohms
	Min Illum.	0.1 - 100.000 Lux (in night color mode 0.01-100.000 Lux)
Audio	Lens	1.4mm fish-eye lens Mega res. (185° view angle)
	Audio Communication	2-way-halfduplex
	Audio Compression	ADPCM 32Kbps
	Frequency	300 Hz - 3.4KHz
	Audio In	Connecting base, line in for microphone
Terminal	Audio Out	Connecting base, line out for external speaker
	Network Interface	Ethernet(10Base-T/100Base-Tx)
	Video Interface	Connecting base, Video composit (NTSC/PAL)
	External Port	Alarm-in x1 / relay-out x1
General	SD Card	SD memory card with the 32GB, 16GB, 8GB, 4GB-64MB.
	Operation Voltage	PoE: 48V, IEEE 802.3af for option (max. 7W) LAN: 12V DC (max. 6W)
	Dimen./Weight	142(H)x142(W)x100(D)mm / @1,000g / 12pcs per carton
	Operation Temp.	-10°C ~ +45°C, relative moisture 20%-90%
	Waterproof	IP66



Pano Secure Software

Order Reference

AXETECH Group Distributor For BENELUX Tél. + 32 2 332 01 11 Fax. + 32 2 332 03 11